

Ultra-High Pressure Foam System



- Delivers 8 gpm (30 L/min) of solution @ 1400 psi (96 BAR)
- Hypro triplex plunger pump provides dependability and high pressure performance
- Exclusive PowerPro™ 13 HP gas engine includes electric start for quick start-up
- Ideal for use with all Class A foam concentrate applications
- Adjustable control provides unmatched accuracy over the widest range of flow
- Dual-action spray gun delivers foam solution over 45 feet (13 meters)
- Thermal relief valve prevents overheating during extended idle
- Adjustable foam percentage selector from 0.3% to 3.0%
- Decreases water usage by more than 40%, and reduces environmental damage
- Incorporates a patented foam concentrate direct injector system, providing better accuracy over the use of inaccurate suction side eductors

Hydraulically-Driven Pressure Washers

Offering 3-4 gpm Cleaning Power



- Anodized, die-cast aluminum crankcase
- Heavy-duty, corrosion-resistant brass manifold
- One-piece, forged-bronze connecting rods
- Stainless steel valves
- Hardened, stainless steel piston guides
- Solid ceramic plungers
- High pressure and low pressure packings of high-quality buna textile
- Heavy-duty, ball bearing supported crankshaft
- Sight glass and oil-level dipstick
- Hydraulic ports: 1/2" NPT inlet, 3/4" NPT outlet

The hydraulically-driven pressure washers are ideally suited for remote and explosion-proof environments where electricity cannot be used. These models are equipped with a hydraulic motor-driven, triplex plunger pump; and include an unloader, gauge, and quick disconnect. Some models include a chemical injector, 50' pressure wash hose, trigger gun and insulated wand with adjustable Hi-Lo and Variable-Angle cleaning nozzle. Certain models are also equipped with a chemical injector. See chart below for details.

| Model Number | Max | Max | Hydraulic Motor Requirements | | Description | Weight |
|--------------|------|-------|------------------------------|-------|--|--------|
| | GPM | PSI | GPM | PSI | | LBS |
| | LPM | BAR | LPM | BAR | | KG |
| 1802C* | 3.0 | 1000 | 5.0 | 1300 | Forged Brass Head Triplex Pumps with hydraulic motor, adjustable unloader, gauge, 1/2" NPT input, 3/8" quick disconnect output | 38 |
| | 11.4 | 68.9 | 18.9 | 89.6 | | 17.2 |
| 1803C | 3.0 | 1000 | 5.0 | 1300 | | 28 |
| | 11.4 | 68.9 | 18.9 | 89.6 | | 12.7 |
| 1804C* | 3.0 | 1500 | 8.0 | 1900 | | 41 |
| | 11.4 | 103.4 | 30.3 | 131.0 | | 18.6 |
| 1805C | 3.0 | 1500 | 8.0 | 1900 | | 26 |
| | 11.4 | 103.4 | 30.3 | 131.0 | | 11.8 |
| 1806C* | 3.0 | 2000 | 11.0 | 1300 | | 41 |
| | 11.4 | 137.9 | 41.6 | 89.6 | | 18.6 |
| 1807C | 3.0 | 2000 | 11.0 | 1300 | Forged Brass Head Triplex Pumps with hydraulic motor, chemical injector, adjustable unloader, gauge, 3/4" GH input, 3/8" quick disconnect output | 26 |
| | 11.4 | 137.9 | 41.6 | 89.6 | | 11.8 |
| 1824C* | 4.0 | 1500 | 8.5 | 2000 | | 49 |
| | 15.1 | 103.4 | 32.2 | 137.9 | | 22.2 |
| 1825C | 4.0 | 1500 | 8.5 | 2000 | | 33 |
| | 15.1 | 103.4 | 32.2 | 137.9 | | 14.9 |
| 1826C* | 4.0 | 2000 | 8.5 | 2000 | | 49 |
| | 15.1 | 137.9 | 32.2 | 137.9 | | 22.2 |
| 1827C | 4.0 | 2000 | 8.5 | 2000 | | 33 |
| | 15.1 | 137.9 | 32.2 | 137.9 | | 14.9 |

*Includes 50 ft. hose and gun assembly.